

FTPOLYMER

122 Chemin de la Cavée - 78630 Orgeval
Tél : +33 (0)1 39 13 20 82 - Fax : +33 (0)1 39 13 33 79

400 SERIES RTV PRODUCTS

Product	Description	Application	Color/ Appearance	Shore Hardness	Viscosity	Tack Time	Full Cure Time	Specific Gravity
400-100	Single component silicone Non-corrosive Paste product	Bond materials as a sealant, without the use of a primer, for creating gaskets or other applications	White	25 +/- 5	45,000-75,000 cps	5-10 min	24 hours	1.15-1.25
400-102	Single component silicone Non-corrosive Paste product	Bond materials as a sealant, without the use of a primer, for creating gaskets or other applications	Black	20 +/- 5	45,000-80,000 cps	5-10 min	24 hours	1.15-1.25
400-103	Single component silicone Non-corrosive Paste product	Bond materials as a sealant, without the use of a primer, for creating gaskets or other applications	Aluminum	20 +/- 5	45,000-75,000 cps	5-10 min	24 hours	1.00-1.05
400-110	Single component silicone Non-corrosive Paste product	Designed for industrial applications and to be used in extreme environmental conditions	Black	20 +/- 5		20 min	20-24 hours	1.04-1.16
400-118	Single component silicone Non-corrosive Paste product	Designed for industrial applications and to be used in extreme environmental conditions	Gray	20 +/- 5		20 min	20-24 hours	1.00-1.50
400-150	Single component silicone Non-corrosive Paste product	Bond materials as a sealant, without the use of a primer, for creating gaskets or other applications	Translucent	20 +/- 5	35,000-70,000 cps	5-10 min	24 hours	1.00-1.05
400-155	Single component silicone Non-corrosive Paste product	Designed for industrial applications and to be used in extreme environmental conditions	Translucent	20 +/- 5		5-15 min	3-6 hours	1.00-1.05
400-195	Single component silicone Non-corrosive Paste product	Assembly applications with fast and early strength needs	Translucent	20 +/- 5	35,000-80,000 cps	4-7 min	24 hours	1.00-1.05
400-196	Single component silicone Non-corrosive Paste product	Assembly applications with fast and early strength needs	Translucent	20 +/- 5	20,000-40,000 cps	4-10 min	24 hours	1.00-1.05
400-202	Single component silicone Non-corrosive Paste product	Assembly applications with fast and early strength needs	Black	20 +/- 5	35,000-80,000 cps	4-7 min	20-24 hours	1.00-1.05
400-590	Single component silicone Non-corrosive Paste product	Designed for industrial applications and to be used in extreme environmental conditions	Black	40 +/- 10		40 min	24 hours	1.25-1.55
400-900	Single component silicone Non-corrosive Paste product	Create formed-in-place gaskets where user re-entry is required	White	40 +/- 10	32,000-55,000 cps	30-40 min	24 hours	1.20-1.30
400-950	Single component silicone Non-corrosive Paste product	Create formed-in-place gaskets where user re-entry is required	White	35 +/- 10	15,000-25,000 cps	30-40 min	24 hours	1.00-1.05